

VertiClean™ PTFE Syringe Filters

VertiClean™ PTFE Syringe Filters

- Filtration of non-aqueous or solvent based samples
- Prewetting with methanol or ethanol prior to aqueous samples filtration
- Available in 13mm and 25mm diameter membranes
- Economic price

VertiClean™ PTFE (polytetrafluoroethylene) is hydrophobic, highest solvent resistance and high protein binding. VertiClean™ PTFE ideals for filtration of non-aqueous or solvent based samples and degassing chromatography.



Specifications			
Properties		Diameter (mm)	
		13	25
Bubble point ¹ (psi)	0.2 µm	14	
	0.45µm	8	
Typical Flow rate ² (mL/min/cm ²)	0.2 µm	55	
	0.45µm	100	
Housing Material		Pigment-free Polypropylene	
Connector (inlet/outlet)		Female Luer Lock/Male Luer Slip	
Burst Pressure ³ (psi)		100	80
Retain Volume ⁴ (µL)		30	125
Sample Volume (mL)		10	150
Packaging	13mm	PP Thread Bottle	
	25mm	Corrugated Box	

¹ Bubble point is the minimum pressure required to force air through a membrane which has been prewet with water.

² Flow rate is initial flow rate at 10 psi using water.

³ Burst pressure is the maximum pressure to force air through a closed outlet end housing.

⁴ Retention volume is a volume of solvent retained inside the housing.

Ordering Information			
Size	Pore Size	QTY	Part No.
VertiClean™ PTFE Syringe Filters			
13mm	0.2 µm	100	0221-2101
		500	0221-2105
		1000	0221-2110
	0.45 µm	100	0221-2301
		500	0221-2305
		1000	0221-2310
25mm	0.2 µm	100	0223-2101
		500	0223-2105
		1000	0223-2110
	0.45 µm	100	0223-2301
		500	0223-2305
		1000	0223-2310