

according to Regulation (EC) No. 1907/2006

Revision Date 19.06.2017

Version 7.1

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator

block with long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 -

0.4 - 0.5 mg/l Cu MColortest™

Cu-1

REACH Registration Number This product is a mixture. REACH Registration Number see section 3.

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Reagent for analysis

For additional information on uses please refer to the Merck Chemicals

portal (www.merckgroup.com).

## 1.3 Details of the supplier of the safety data sheet

Company Merck KGaA \* 64271 Darmstadt \* Germany \* Phone:+49 6151 72-0

Responsible Department LS-QHC \* e-mail: prodsafe@merckgroup.com

1.4 Emergency telephone

number

Please contact the regional company representation in your country.

#### **SECTION 2. Hazards identification**

# 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2, H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



# according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-1

Signal word

Warning

Hazard statements

H319 Causes serious eye irritation.

Precautionary statements

Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

# Reduced labelling (≤125 ml)

Hazard pictograms



Signal word
Warning

# 2.3 Other hazards

None known.

# SECTION 3. Composition/information on ingredients

Chemical nature

Mixture of solid substances

3.1 Substance

Not applicable

3.2 Mixture

# according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-1

## Hazardous components (REGULATION (EC) No 1272/2008)

Chemical name (Concentration)

CAS-No. Registration number Classification

sodium carbonate (>= 10 % - < 20 %)

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

497-19-8 01-2119485498-19-

XXXX Eye irritation, Category 2, H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

### **SECTION 4. First aid measures**

### 4.1 Description of first aid measures

After inhalation: fresh air.

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/shower.

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

## 4.2 Most important symptoms and effects, both acute and delayed

The following applies to ammonium salts in general: after swallowing: local irritation symptoms, nausea, vomiting, diarrhoea. Systemic effect: after the uptake of very large qantities: drop in blood pressure, collapse, CNS disorders, spasms, narcotic conditions, respiratory paralysis, haemolysis.

irritant effects

#### 4.3 Indication of any immediate medical attention and special treatment needed

No information available.

## **SECTION 5. Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media

Water, Foam, Carbon dioxide (CO2), Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

# 5.2 Special hazards arising from the substance or mixture

Combustible.

Development of hazardous combustion gases or vapours possible in the event of fire.

Fire may cause evolution of:

# according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-1

nitrogen oxides

#### 5.3 Advice for firefighters

Special protective equipment for firefighters

In the event of fire, wear self-contained breathing apparatus.

Further information

Suppress (knock down) gases/vapours/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

#### SECTION 6. Accidental release measures

## 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

## 6.2 Environmental precautions

Do not let product enter drains.

## 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

#### 6.4 Reference to other sections

Indications about waste treatment see section 13.

# SECTION 7. Handling and storage

## 7.1 Precautions for safe handling

Advice on safe handling

Observe label precautions.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance.

## 7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed.

Recommended storage temperature see product label.

The data applies to the entire pack.

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

## according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-1

### SECTION 8. Exposure controls/personal protection

## 8.1 Control parameters

## Derived No Effect Level (DNEL)

sodium carbonate (497-19-8)

Worker DNEL, Local effects inhalation 10 mg/m³

longterm

## Predicted No Effect Concentration (PNEC)

sodium carbonate (497-19-8)

PNEC no data available

#### 8.2 Exposure controls

### **Engineering measures**

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

#### Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Eye/face protection Safety glasses

Hand protection

full contact:

Glove material: Nitrile rubber
Glove thickness: 0,11 mm
Break through time: > 480 min

splash contact:

Glove material: Nitrile rubber Glove thickness: 0,11 mm
Break through time: > 480 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 741 Dermatril® L (full contact), KCL 741 Dermatril® L (splash contact).

This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment protective clothing

## according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-1

### Respiratory protection

required when dusts are generated.

Recommended Filter type: Filter P 2 (acc. to DIN 3181) for solid and liquid particles of harmful substances

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

## Environmental exposure controls

Do not let product enter drains.

Upper explosion limit

## SECTION 9. Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

Form crystalline

Colour white

Odour ammoniacal

Odour Threshold No information available.

pH No information available.

Melting point No information available.

Boiling point No information available.

Flash point No information available.

Evaporation rate No information available.

Flammability (solid, gas) No information available.

Lower explosion limit No information available.

No information available.

Vapour pressure No information available.

Relative vapour density No information available.

Density No information available.

Relative density No information available.

# according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-1

Water solubility soluble

Partition coefficient: n-

octanol/water

No information available.

Auto-ignition temperature No information available.

Decomposition temperature No information available.

Viscosity, dynamic No information available.

Explosive properties Not classified as explosive.

Oxidizing properties none

#### 9.2 Other data

none

### SECTION 10. Stability and reactivity

#### 10.1 Reactivity

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

## 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

## 10.3 Possibility of hazardous reactions

Violent reactions possible with:

strong oxidising agents, Aluminium, Alkaline earth metals, organic nitro compounds, Fluorine, Alkali metals, nonmetallic oxides, conc. sulfuric acid

# 10.4 Conditions to avoid

Strong heating (decomposition).

# 10.5 Incompatible materials

no information available

## 10.6 Hazardous decomposition products

in the event of fire: See section 5.

## **SECTION 11. Toxicological information**

## 11.1 Information on toxicological effects

### Mixture

Acute oral toxicity

Symptoms: Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract.

# according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-1

Acute inhalation toxicity

Symptoms: Possible symptoms:, mucosal irritations

Acute dermal toxicity

This information is not available.

Skin irritation

Possible damages: slight irritation

Eye irritation

Mixture causes serious eye irritation.

Sensitisation

This information is not available.

Germ cell mutagenicity

This information is not available.

Carcinogenicity

This information is not available.

Reproductive toxicity

This information is not available.

Teratogenicity

This information is not available.

Specific target organ toxicity - single exposure

This information is not available.

Specific target organ toxicity - repeated exposure

This information is not available.

Aspiration hazard

This information is not available.

### 11.2 Further information

The following applies to ammonium salts in general: after swallowing: local irritation symptoms, nausea, vomiting, diarrhoea. Systemic effect: after the uptake of very large qantities: drop in blood pressure, collapse, CNS disorders, spasms, narcotic conditions, respiratory paralysis, haemolysis.

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

## Components

sodium carbonate

Acute oral toxicity

LD50 Rat: 2.800 mg/kg (ECHA) LDLO human: 714 mg/kg (RTECS)

Acute dermal toxicity
LD50 Rabbit: > 2.000 mg/kg

**US-EPA** 

# according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-1

Skin irritation

Rabbit

Result: No skin irritation OECD Test Guideline 404

Eye irritation Rabbit

Result: Eye irritation

US-EPA

Germ cell mutagenicity Genotoxicity in vitro Ames test Escherichia coli Result: negative

(Lit.)

# **SECTION 12. Ecological information**

#### **Mixture**

# 12.1 Toxicity

No information available.

# 12.2 Persistence and degradability

No information available.

## 12.3 Bioaccumulative potential

No information available.

## 12.4 Mobility in soil

No information available.

# 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.

## 12.6 Other adverse effects

Discharge into the environment must be avoided.

## Components

sodium carbonate

Toxicity to fish

static test LC50 Lepomis macrochirus (Bluegill sunfish): 300 mg/l; 96 h (ECHA)

Toxicity to daphnia and other aquatic invertebrates semi-static test EC50 Ceriodaphnia dubia (water flea): 220 - 227 mg/l; 48 h US-EPA

Biodegradability

The methods for determining the biological degradability are not applicable to inorganic substances.

Partition coefficient: n-octanol/water Not applicable

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

## according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-1

# **SECTION 13. Disposal considerations**

Waste treatment methods

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

## **SECTION 14. Transport information**

Land transport (ADR/RID)

**14.1 - 14.6** Not classified as dangerous in the meaning of transport

regulations.

Inland waterway transport (ADN)

Not relevant

Air transport (IATA)

**14.1 - 14.6** Not classified as dangerous in the meaning of transport

regulations.

Sea transport (IMDG)

**14.1 - 14.6** Not classified as dangerous in the meaning of transport

regulations.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

THIS TRANSPORT DATA APPLIES TO THE ENTIRE PACK!

### **SECTION 15. Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Major Accident Hazard

96/82/EC

Legislation

Directive 96/82/EC does not apply

SEVESO III Not applicable

Occupational restrictions

Take note of Dir 94/33/EC on the protection of young people at

work.

Regulation (EC) No 1005/2009 on substances that not regulated

deplete the ozone layer

not regulated

Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on

persistent organic pollutants and amending

Directive 79/117/EEC

# according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-1

Substances of very high concern (SVHC)

This product does not contain substances

of very high concern according to

Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of  $\geq$  0.1 % (w/w).

National legislation

Storage class 10 - 13 The data applies to the entire pack.

# 15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out.

## **SECTION 16. Other information**

# Full text of H-Statements referred to under sections 2 and 3.

H319 Causes serious eye irritation.

## Training advice

Provide adequate information, instruction and training for operators.

## Labelling

Hazard pictograms



Signal word

Warning

Hazard statements

H319 Causes serious eye irritation.

Precautionary statements

# according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-1

## Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

# Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

## Regional representation

This information is given on the authorised Safety Data Sheet for your country.

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.



according to Regulation (EC) No. 1907/2006

Revision Date 19.06.2017

Version 7.1

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator

block with long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 -

0.4 - 0.5 mg/l Cu MColortest™

Cu-2

REACH Registration Number This product is a mixture. REACH Registration Number see section 3.

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Reagent for analysis

For additional information on uses please refer to the Merck Chemicals

portal (www.merckgroup.com).

# 1.3 Details of the supplier of the safety data sheet

Company Merck KGaA \* 64271 Darmstadt \* Germany \* Phone:+49 6151 72-0

Responsible Department LS-QHC \* e-mail: prodsafe@merckgroup.com

1.4 Emergency telephone

number

Please contact the regional company representation in your country.

#### **SECTION 2. Hazards identification**

### 2.1 Classification of the substance or mixture

This mixture is not classified as dangerous according to European Union legislation.

#### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

#### 2.3 Other hazards

None known.

## SECTION 3. Composition/information on ingredients

# according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-2

Chemical nature

Solution in DMSO.

## 3.1 Substance

Not applicable

#### 3.2 Mixture

Remarks No disclosure requirement according to Regulation (EC) No.

1907/2006.

#### **SECTION 4. First aid measures**

#### 4.1 Description of first aid measures

After inhalation: fresh air.

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/shower.

After eye contact: rinse out with plenty of water. Remove contact lenses.

After swallowing: make victim drink water (two glasses at most). Consult doctor if feeling unwell.

Subsequently administer: activated charcoal (20 - 40 g in 10% slurry).

## 4.2 Most important symptoms and effects, both acute and delayed

irritant effects, Nausea, Headache, Tiredness, CNS disorders

# 4.3 Indication of any immediate medical attention and special treatment needed

Laxative: Sodium sulfate (1 tablespoon/1/4 I water). Get medical attention.

# **SECTION 5. Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media

Water, Foam, Carbon dioxide (CO2), Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

# 5.2 Special hazards arising from the substance or mixture

Combustible.

Forms explosive mixtures with air on intense heating.

Vapours are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Fire may cause evolution of:

# according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-2

Sulphur oxides

#### 5.3 Advice for firefighters

Special protective equipment for firefighters

In the event of fire, wear self-contained breathing apparatus.

Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapours/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

#### SECTION 6. Accidental release measures

## 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapours, aerosols. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

#### 6.2 Environmental precautions

Do not let product enter drains.

### 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

## 6.4 Reference to other sections

Indications about waste treatment see section 13.

## SECTION 7. Handling and storage

## 7.1 Precautions for safe handling

Advice on safe handling

Observe label precautions.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance.

# 7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed.

Recommended storage temperature see product label.

## according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-2

The data applies to the entire pack.

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

#### SECTION 8. Exposure controls/personal protection

## 8.1 Control parameters

#### 8.2 Exposure controls

## **Engineering measures**

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

### Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Eye/face protection Safety glasses

Hand protection

full contact:

Glove material: polychloroprene

Glove thickness: 0,65 mm Break through time: > 480 min

splash contact:

Glove material: natural latex
Glove thickness: 0,6 mm
Break through time: > 240 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 720 Camapren® (full contact), KCL 706 Lapren® (splash contact).

This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective

# according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-2

devices are carried out according to the instructions of the producer. These measures have to be properly documented.

# Environmental exposure controls

Do not let product enter drains.

## SECTION 9. Physical and chemical properties

# 9.1 Information on basic physical and chemical properties

Form liquid

Colour colourless

Odour odourless

Odour Threshold Not applicable

pH No information available.

Melting point No information available.

Boiling point No information available.

Flash point 87 °C

Method: c.c.

Evaporation rate No information available.

Flammability (solid, gas) No information available.

Lower explosion limit No information available.

Upper explosion limit No information available.

Vapour pressure No information available.

Relative vapour density No information available.

Density No information available.

Relative density No information available.

Water solubility at 20 °C

soluble

# according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-2

Partition coefficient: n-

octanol/water

log Pow: -1,35 (experimental)

Bioaccumulation is not expected. (Lit.) (refers to pure

substance)

Auto-ignition temperature No information available.

Decomposition temperature No information available.

Viscosity, dynamic No information available.

Explosive properties Not classified as explosive.

Oxidizing properties none

9.2 Other data

Ignition temperature

300 - 302 °C (Dimethylsulfoxide)

## SECTION 10. Stability and reactivity

### 10.1 Reactivity

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

## 10.2 Chemical stability

hygroscopic

# 10.3 Possibility of hazardous reactions

Risk of explosion with:

acetylidene, organic halides, perchlorates, Acid chlorides, nonmetallic halides, iron(III) compounds, nitrates, fluorides, chlorates, hydrides, perchloric acid, Oxides of phosphorus, Nitric acid, silver compounds, silicon compounds, silanes, acid halides

Exothermic reaction with:

boron compounds, oxyhalogenic compounds, Potassium, sodium, Strong oxidizing agents, phosphorus halides, strong reducing agents, Acid chlorides, Strong acids, silver salt, nitrogen dioxide

Risk of ignition or formation of inflammable gases or vapours with:

potassium permanganate

## 10.4 Conditions to avoid

Strong heating.

## 10.5 Incompatible materials

various plastics, Metals

# according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-2

# 10.6 Hazardous decomposition products

in the event of fire: See section 5.

## **SECTION 11. Toxicological information**

# 11.1 Information on toxicological effects

**Mixture** 

Acute oral toxicity

This information is not available.

Acute inhalation toxicity

This information is not available.

Acute dermal toxicity

absorption

Skin irritation

Possible damages: slight irritation

Eye irritation

Possible damages: slight irritation

Sensitisation

This information is not available.

Germ cell mutagenicity

This information is not available.

Carcinogenicity

This information is not available.

Reproductive toxicity

This information is not available.

Teratogenicity

This information is not available.

Specific target organ toxicity - single exposure

This information is not available.

Specific target organ toxicity - repeated exposure

This information is not available.

Aspiration hazard

This information is not available.

## 11.2 Further information

Possible symptoms:

After uptake:

CNS disorders, Nausea, Tiredness, Headache

Possible damages:

Damage to:

Liver, Kidney

However, when the product is handled appropriately, hazardous effects are unlikely to occur.

Handle in accordance with good industrial hygiene and safety practice.

# according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-2

## **SECTION 12. Ecological information**

### **Mixture**

#### 12.1 Toxicity

No information available.

#### 12.2 Persistence and degradability

No information available.

#### 12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water

log Pow: -1,35 (experimental)

Bioaccumulation is not expected. (Lit.) (refers to pure substance)

### 12.4 Mobility in soil

No information available.

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.

#### 12.6 Other adverse effects

Additional ecological information

Discharge into the environment must be avoided.

## **SECTION 13. Disposal considerations**

Waste treatment methods

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

### **SECTION 14. Transport information**

# Land transport (ADR/RID)

**14.1 - 14.6** Not classified as dangerous in the meaning of transport

regulations.

#### Inland waterway transport (ADN)

Not relevant

Air transport (IATA)

**14.1 - 14.6** Not classified as dangerous in the meaning of transport

regulations.

Sea transport (IMDG)

## according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-2

**14.1 - 14.6** Not classified as dangerous in the meaning of transport

regulations.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

THIS TRANSPORT DATA APPLIES TO THE ENTIRE PACK!

## **SECTION 15. Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Major Accident Hazard 96/82/EC

Legislation Directive 96/82/EC does not apply

SEVESO III Not applicable

Occupational restrictions Take note of Dir 94/33/EC on the protection of young people at

work.

Regulation (EC) No 1005/2009 on substances that not regulated

deplete the ozone layer

Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on

Substances of very high concern (SVHC)

persistent organic pollutants and amending

Directive 79/117/EEC

of very high concern according to

not regulated

Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory

This product does not contain substances

concentration limit of  $\geq 0.1 \%$  (w/w).

National legislation

Storage class 10 - 13 The data applies to the entire pack.

#### 15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out.

# according to Regulation (EC) No. 1907/2006

Catalogue No. 114414

Product name Copper Test Method: colorimetric with color card and comparator block with

long test tubes 0.05 - 0.08 - 0.12 - 0.16 - 0.20 - 0.25 - 0.3 - 0.4 - 0.5 mg/l Cu

MColortest™

Cu-2

#### **SECTION 16. Other information**

Full text of H-Statements referred to under sections 2 and 3.

## Training advice

Provide adequate information, instruction and training for operators.

## Labelling

Signal word

Warning

Hazard statements

H227 Combustible liquid.

# Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

# Regional representation

This information is given on the authorised Safety Data Sheet for your country.

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.