

according to Regulation (EC) No. 1907/2006

Revision Date 18.07.2018

Version 10.1

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in

HNO₃ 1 mol/l 1000 mg/l Sc Certipur®

REACH Registration Number This product is a mixture. REACH Registration Number see section 3.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Reagent for analysis

For additional information on uses please refer to the Merck Chemicals

portal (www.merckgroup.com).

1.3 Details of the supplier of the safety data sheet

Company Merck KGaA * 64271 Darmstadt * Germany * Phone:+49 6151 72-0

Responsible Department LS-QHC * e-mail: prodsafe@merckgroup.com

1.4 Emergency telephone

Please contact the regional company representation in your country.

number

SECTION 2. Hazards identification

2.1 Classification of the substance or mixture Classification (REGULATION (EC) No 1272/2008)

Corrosive to metals, Category 1, H290

Skin corrosion, Category 1B, H314

For the full text of the H-Statements mentioned in this Section, see Section 16.

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

Danger

Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

EUH071 Corrosive to the respiratory tract.

Precautionary statements

Prevention

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308 + P310 IF exposed or concerned: immediately call a POISON CENTER or doctor/ physician.

Reduced labelling (≤125 ml)

Hazard pictograms



Signal word

Danger

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

Hazard statements

H314 Causes severe skin burns and eye damage.

Precautionary statements

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P310 IF exposed or concerned: immediately call a POISON CENTER or doctor/ physician.

Contains: nitric acid

2.3 Other hazards

None known.

SECTION 3. Composition/information on ingredients

Chemical nature Nitric acid solution.

3.1 Substance

Not applicable

3.2 Mixture

Hazardous components (REGULATION (EC) No 1272/2008)

Chemical name (Concentration)

CAS-No. Registration number Classification

nitric acid (>= 5% - < 10%)

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

7697-37-2 01-2119487297-23-

XXXX Oxidizing liquid, Category 2, H272

Corrosive to metals, Category 1, H290

Acute toxicity, Category 1, H330 Skin corrosion, Category 1A, H314

For the full text of the H-Statements mentioned in this Section, see Section 16.

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

SECTION 4. First aid measures

4.1 Description of first aid measures

General advice

First aider needs to protect himself.

After inhalation: fresh air. Call in physician.

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician immediately.

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

Irritation and corrosion, Cough, Shortness of breath, Bloody vomiting, death

Risk of blindness!

The following applies to nitrites/nitrates in general: methaemoglobinaemia after the uptake of large quantities.

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Not combustible.

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

Ambient fire may liberate hazardous vapours.

Fire may cause evolution of:

nitrogen oxides, nitrous gases

5.3 Advice for firefighters

Special protective equipment for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Suppress (knock down) gases/vapours/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10).

Take up with liquid-absorbent and neutralising material (e.g. Chemizorb® H⁺, Merck Art. No. 101595). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

Indications about waste treatment see section 13.

SECTION 7. Handling and storage

7.1 Precautions for safe handling

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

Advice on safe handling

Observe label precautions.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

No metal containers.

Storage conditions

Tightly closed.

Recommended storage temperature see product label.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL)

nitric acid (7697-37-2)

Worker DNEL, Local effects inhalation 1,3 mg/m³

longterm

Predicted No Effect Concentration (PNEC)

nitric acid (7697-37-2)

PNEC no data available

8.2 Exposure controls

Engineering measures

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Eye/face protection

Tightly fitting safety goggles

Hand protection

full contact:

Glove material: Nitrile rubber

Glove thickness: 0,11 mm

Break through time: 480 min

splash contact:

Glove material: Viton (R)
Glove thickness: 0,70 mm
Break through time: 30 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 741 Dermatril® L (full contact), KCL 890 Vitoject® (splash contact).

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment

Acid-resistant protective clothing

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

Respiratory protection

required when vapours/aerosols are generated.

Recommended Filter type: filter E-(P2)

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not let product enter drains.

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form liquid

Colour colourless

Odour odourless

Odour Threshold Not applicable

pH ca. 0

at 20 °C

Melting point No information available.

Boiling point No information available.

Flash point Not applicable

Evaporation rate No information available.

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

Flammability (solid, gas) No information available.

Lower explosion limit Not applicable

Upper explosion limit Not applicable

Vapour pressure No information available.

Relative vapour density No information available.

Density ca.1,031 g/cm3

at 20 °C

Relative density No information available.

Water solubility No information available.

Partition coefficient: n-

octanol/water

No information available.

Auto-ignition temperature No information available.

Decomposition temperature No information available.

Viscosity, dynamic No information available.

Explosive properties Not classified as explosive.

Oxidizing properties Oxidizing potential

9.2 Other data

Corrosion May be corrosive to metals.

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

SECTION 10. Stability and reactivity

10.1 Reactivity

Oxidizing agents

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion with:

Risk of ignition or formation of inflammable gases or vapours with:

Alkali metals, Alkaline earth metals, Ammonia, alkalines, hydrides, halogens, halogen compounds, nonmetallic oxides, nonmetallic halides, nonmetallic hydrogen compounds, nonmetals, phosphides, nitrides, lithium silicide, hydrogen peroxide, organic combustible substances, oxidisable substances, organic solvent, Alcohols, Ketones, Aldehydes, anhydrides, Amines, anilines, Nitriles, organic nitro compounds, hydrazine and derivatives, acetylidene, Metals, metal alloys, metallic oxides, acids, Fluorine

Generates dangerous gases or fumes in contact with:

Copper, Mercury

10.4 Conditions to avoid

no information available

10.5 Incompatible materials

Cellulose

Metals

Contact with metals may lead to the formation of nitrous gases and hydrogen.

10.6 Hazardous decomposition products

in the event of fire: See section 5.

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

SECTION 11. Toxicological information

11.1 Information on toxicological effects

Mixture

Acute oral toxicity

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.

Acute inhalation toxicity

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract, After a latency period:, Inhalation may lead to the formation of oedemas in the respiratory tract.

Acute dermal toxicity

This information is not available.

Skin irritation

Mixture causes burns.

Eye irritation

Mixture causes serious eye damage. Risk of blindness!

Sensitisation

This information is not available.

Germ cell mutagenicity

This information is not available.

Carcinogenicity

This information is not available.

Reproductive toxicity

This information is not available.

Teratogenicity

This information is not available.

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

Specific target organ toxicity - single exposure

This information is not available.

Specific target organ toxicity - repeated exposure

This information is not available.

Aspiration hazard

This information is not available.

11.2 Further information

After uptake:

Systemic effects:

Bloody vomiting, strong pain (risk of perforation!), tissue damage, death

The following applies to nitrites/nitrates in general: methaemoglobinaemia after the uptake of

large quantities.

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Components

nitric acid

Acute inhalation toxicity

LC50 Rat: > 2,65 mg/l; 4 h; vapour

OECD Test Guideline 403

Germ cell mutagenicity

Genotoxicity in vitro

Ames test

Salmonella typhimurium

Result: negative

Method: OECD Test Guideline 471

SECTION 12. Ecological information

Mixture

12.1 Toxicity

No information available.

12.2 Persistence and degradability

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Substance(s) in the mixture do(es) not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII, or a PBT/vPvB assessment was not conducted.

12.6 Other adverse effects

Additional ecological information

Biological effects:

Harmful effect due to pH shift. Forms corrosive mixtures with water even if diluted. Does not cause biological oxygen deficit. Hazard for drinking water supplies.

Depending on the concentration, phosphorus and/or nitrogen compounds may contribute to the eutrophication of drinking- water supplies.

Discharge into the environment must be avoided.

Components

nitric acid

Biodegradability

The methods for determining the biological degradability are not applicable to inorganic substances.

Partition coefficient: n-octanol/water

log Pow: -2,3

OECD Test Guideline 107

Bioaccumulation is not expected.

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

Henry constant
2482 Pa*m³/mol

Method: (calculated)

(Lit.) Distribution preferentially in air.

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

SECTION 13. Disposal considerations

Waste treatment methods

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14. Transport information

Land transport (ADR/RID)

14.1 UN number UN 2031

14.2 Proper shipping name NITRIC ACID

14.3 Class 8

14.4 Packing group

14.5 Environmentally hazardous --

14.6 Special precautions for yes

user

Tunnel restriction code E

Inland waterway transport (ADN)

Not relevant

Air transport (IATA)

14.1 UN number UN 2031

14.2 Proper shipping name NITRIC ACID

14.3 Class 8

14.4 Packing group

14.5 Environmentally hazardous --

14.6 Special precautions for yes

user Not permitted for transport

Sea transport (IMDG)

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

14.1 UN number UN 2031

14.2 Proper shipping name NITRIC ACID NOT MORE THAN 20%

14.3 Class 8

14.4 Packing group

14.5 Environmentally hazardous --

14.6 Special precautions for yes

user

EmS F-A S-B

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Major Accident Hazard SEVESO III
Legislation Not applicable

Occupational restrictions Take note of Dir 94/33/EC on the protection of young people at

work.

Regulation (EC) No 1005/2009 on substances that not regulated

deplete the ozone layer

Regulation (EC) No 850/2004 of the European not regulated

Parliament and of the Council of 29 April 2004 on

persistent organic pollutants and amending

Directive 79/117/EEC

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

Substances of very high concern (SVHC)

This product does not contain substances

of very high concern according to

Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory

concentration limit of ≥ 0.1 % (w/w).

National legislation

Storage class 8B

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out.

SECTION 16. Other information

Full text of H-Statements referred to under sections 2 and 3.

H272 May intensify fire; oxidizer. H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H330 Fatal if inhaled.

Training advice

Provide adequate information, instruction and training for operators.

Labelling

Hazard pictograms



Signal word

Danger

Hazard statements

H290 May be corrosive to metals.

according to Regulation (EC) No. 1907/2006

Catalogue No. 119513

Product name Scandium standard solution traceable to SRM from NIST Sc₂O₃ in HNO₃ 1

mol/I 1000 mg/I Sc Certipur®

H314 Causes severe skin burns and eye damage.

Precautionary statements

Prevention

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308 + P310 IF exposed or concerned: immediately call a POISON CENTER or doctor/ physician.

Contains: nitric acid

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Regional representation

This information is given on the authorised Safety Data Sheet for your country.

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.