

according to Regulation (EC) No. 1907/2006

Revision Date 25.07.2019

Version 2.4

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Catalogue No. 845088

Product name Ethylamine (70% solution in water) Msynth®plus

REACH Registration This product is a mixture. REACH Registration Number see

Number section 3.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Pharmaceutical production, Chemical for synthesis

Intermediate for use under strictly controlled conditions For additional information on uses please refer to the Merck

Chemicals portal (www.merckgroup.com).

1.3 Details of the supplier of the safety data sheet

Company Merck KGaA * 64271 Darmstadt * Germany * Phone: +49

6151 72-0

Responsible Department LS-QHC * e-mail: prodsafe@merckgroup.com

1.4 Emergency telephone Please contact the regional company representation in

number your country.

SECTION 2. Hazards identification

2.1 Classification of the substance or mixture Classification (REGULATION (EC) No 1272/2008)

Flammable liquid, Category 2, H225

Acute toxicity, Category 4, Oral, H302

Acute toxicity, Category 3, Inhalation, H331

Acute toxicity, Category 3, Dermal, H311

Skin corrosion, Category 1B, H314

Specific target organ toxicity - single exposure, Category 3, Respiratory system, H335

For the full text of the H-Statements mentioned in this Section, see Section 16.

according to Regulation (EC) No. 1907/2006

Catalogue No. 845088

Product name Ethylamine (70% solution in water) Msynth®plus

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H311 + H331 Toxic in contact with skin or if inhaled.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

Precautionary statements

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground/bond container and receiving equipment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P310 IF exposed or concerned: immediately call a POISON CENTER or doctor/physician.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Reduced labelling (≤125 ml)

Hazard pictograms







Signal word Danger

Hazard statements

H311 + H331 Toxic in contact with skin or if inhaled.

H314 Causes severe skin burns and eye damage.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Page 2 of 14

according to Regulation (EC) No. 1907/2006

Catalogue No. 845088

Product name Ethylamine (70% solution in water) Msynth®plus

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308 + P310 IF exposed or concerned: immediately call a POISON CENTER or doctor/ physician.

Contains: Ethylamine

2.3 Other hazards

None known.

SECTION 3. Composition/information on ingredients

Chemical nature

Aqueous solution

3.1 Substance

Not applicable

3.2 Mixture

Hazardous components (REGULATION (EC) No 1272/2008)

Chemical name (Concentration)

CAS-No. Registration Classification

number

Ethylamine (>= 50 % - <= 100 %)

75-04-7 *) Flammable gases, Category 1, H220

Eye irritation, Category 2, H319

Specific target organ toxicity - single exposure, Category

3, H335

Gases under pressure, Liquefied gas, H280

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4. First aid measures

4.1 Description of first aid measures

General advice

First aider needs to protect himself.

After inhalation: fresh air. Immediately call in physician. If breathing stops:

immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

Page 3 of 14

^{*)} A registration number is not available for this substance as the substance or its use are exempted from registration according to Article 2 REACH Regulation (EC) No 1907/2006, the annual tonnage does not require a registration or the registration is envisaged for a later registration deadline.

according to Regulation (EC) No. 1907/2006

Catalogue No. 845088

Product name Ethylamine (70% solution in water) Msynth®plus

4.2 Most important symptoms and effects, both acute and delayed

Risk of corneal clouding.

Irritation and corrosion, Cough, Shortness of breath

Risk of blindness!

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam, Dry powder

Unsuitable extinguishing media

Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

Combustible.

Pay attention to flashback.

Vapours are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

Fire may cause evolution of:

nitrogen oxides

5.3 Advice for firefighters

Special protective equipment for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapours/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Page 4 of 14

according to Regulation (EC) No. 1907/2006

Catalogue No. 845088

Product name Ethylamine (70% solution in water) Msynth®plus

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

Indications about waste treatment see section 13.

SECTION 7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Observe label precautions.

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorised persons.

Recommended storage temperature see product label.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

The product is registered for use under strictly controlled conditions as defined in Article 18(4) of Regulation (EC) No. 1907/2006 (REACH) and must therefore be handled as such. Refer to the industry guidance prepared by Concawe, Cefic and EFCG for advice on the confirmation of strictly controlled conditions

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

according to Regulation (EC) No. 1907/2006

Catalogue No. 845088

Product name Ethylamine (70% solution in water) Msynth®plus

Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Eye/face protection

Tightly fitting safety goggles

Hand protection

full contact:

Glove material: butyl-rubber
Glove thickness: 0,7 mm
Break through time: 480 min

splash contact:

Glove material: natural latex Glove thickness: 0,6 mm Break through time: 30 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 898 Butoject® (full contact), KCL 706 Lapren® (splash contact).

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Recommended Filter type: Filter K (acc. to DIN 3181) for NH₃

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Environmental exposure controls

Do not let product enter drains.

Risk of explosion.

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form liquid

Colour colourless

according to Regulation (EC) No. 1907/2006

Catalogue No. 845088

Product name Ethylamine (70% solution in water) Msynth®plus

Odour stinging

Odour Threshold No information available.

pH > 14

at 20 °C

Melting point < -70 °C

Boiling point/boiling range 39 °C

at 1.013 hPa

Flash point -26 °C

Method: DIN 51755 Part 1

Evaporation rate No information available.

Flammability (solid, gas) No information available.

Lower explosion limit 3,0 %(V)

Upper explosion limit 12,8 %(V)

Vapour pressure 460 hPa

at 20 °C

Relative vapour density No information available.

Density 0,81 g/cm3

at 20 °C

Relative density No information available.

Water solubility at 20 °C

soluble

Partition coefficient: n-

octanol/water

log Pow: -0,27 (23 °C)

OECD Test Guideline 107

Bioaccumulation is not expected.

Auto-ignition temperature No information available.

Decomposition temperature No information available.

Viscosity, dynamic No information available.

Explosive properties Not classified as explosive.

Oxidizing properties none

9.2 Other data

according to Regulation (EC) No. 1907/2006

Catalogue No. 845088

Product name Ethylamine (70% solution in water) Msynth®plus

Ignition temperature 375 °C

Method: DIN 51794

SECTION 10. Stability and reactivity

10.1 Reactivity

Vapours may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Violent reactions possible with:

Acid anhydrides, Strong oxidizing agents, Alcohols, Aldehydes, carbon dioxide, acids

Risk of ignition or formation of inflammable gases or vapours with:

sulphur dioxide, hydrogen sulphide

Caution! In contact with nitrites, nitrates, nitrous acid possible liberation of nitrosamines!

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

Aluminium, Copper, Zinc, Tin

10.6 Hazardous decomposition products

in the event of fire: See section 5.

SECTION 11. Toxicological information

11.1 Information on toxicological effects Mixture

Acute oral toxicity LD50 Rat: 400 mg/kg

(External MSDS)

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger

of perforation of the oesophagus and the stomach.

Acute inhalation toxicity LC50 Rat: 5,45 mg/l; 4 h

(External MSDS)

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:,

damage of respiratory tract, Lung oedema

Acute dermal toxicity LD50 Rabbit: 265 mg/kg

(External MSDS)

according to Regulation (EC) No. 1907/2006

Catalogue No. 845088

Product name Ethylamine (70% solution in water) Msynth®plus

Skin irritation

Rabbit

Result: Causes burns.

(External MSDS)

Mixture causes burns.

Eye irritation

Risk of corneal clouding.

Mixture causes serious eye damage. Risk of blindness!

Sensitisation

This information is not available.

Germ cell mutagenicity

This information is not available.

Carcinogenicity

This information is not available.

Reproductive toxicity

This information is not available.

Teratogenicity

This information is not available.

Specific target organ toxicity - single exposure

Mixture may cause respiratory irritation.

Target Organs: Respiratory system

Specific target organ toxicity - repeated exposure

This information is not available.

Aspiration hazard

This information is not available.

11.2 Further information

After absorption:

We have no description of any symptoms of toxicity.

Under given conditions, contact with nitrites or nitric acid can lead to the formation of nitrosamines, which have shown themselves to be carcinogenic in animal experiments.

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Components

Ethylamine

Eye irritation

Rabbit

Result: Eye irritation

(RTECS)

Germ cell mutagenicity

according to Regulation (EC) No. 1907/2006

Catalogue No. 845088

Product name Ethylamine (70% solution in water) Msynth®plus

Genotoxicity in vitro Ames test Result: negative

(Lit.)

SECTION 12. Ecological information

Mixture

12.1 Toxicity

Toxicity to fish

LC50 Leuciscus idus (Golden orfe): 240 mg/l; 96 h

(External MSDS)

Toxicity to daphnia and other aquatic invertebrates EC50 Daphnia magna (Water flea): 94 mg/l; 24 h

(External MSDS)

Toxicity to bacteria

ECO Pseudomonas putida: 5,3 mg/l; 16 h

(External MSDS)

12.2 Persistence and degradability

Biodegradability

60 - 70 %; 28 d

OECD Test Guideline 301F

Readily biodegradable

Biochemical Oxygen Demand (BOD)

1.300 mg/g (5 d)

(External MSDS)

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water

log Pow: -0,27 (23 °C) OECD Test Guideline 107

Bioaccumulation is not expected.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Substance(s) in the mixture do(es) not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII, or a PBT/vPvB assessment was not conducted.

12.6 Other adverse effects

Additional ecological information

Harmful effect due to pH shift.

Discharge into the environment must be avoided.

Components

Ethylamine

Toxicity to fish LC50 Oryzias latipes (Orange-red killifish): 1.000 mg/l; 48 h (ECOTOX Database)

Page 10 of 14

according to Regulation (EC) No. 1907/2006

Catalogue No. 845088

Product name Ethylamine (70% solution in water) Msynth®plus

Toxicity to daphnia and other aquatic invertebrates EC50 Daphnia magna (Water flea): 94 mg/l; 24 h (ECOTOX Database)

SECTION 13. Disposal considerations

Waste treatment methods

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14. Transport information

Land transport (ADR/RID)

14.1 UN number UN 2270

14.2 Proper shipping ETHYLAMINE, AQUEOUS SOLUTION

name

14.3 Class 3(8)14.4 Packing group Η 14.5 Environmentally

hazardous

14.6 Special precautions yes

for user

Tunnel restriction code D/E

Inland waterway transport (ADN)

Not relevant

Air transport (IATA)

14.1 UN number UN 2270

14.2 Proper shipping ETHYLAMINE, AQUEOUS SOLUTION

name

14.3 Class 3(8)14.4 Packing group Η 14.5 Environmentally

hazardous

14.6 Special precautions no

for user

Sea transport (IMDG)

14.1 UN number UN 2270

ETHYLAMINE, AQUEOUS SOLUTION 14.2 Proper shipping

name

14.3 Class 3(8)14.4 Packing group H 14.5 Environmentally

hazardous

Page 11 of 14

according to Regulation (EC) No. 1907/2006

Catalogue No. 845088

Product name Ethylamine (70% solution in water) Msynth®plus

14.6 Special precautions yes

for user

EmS F-E S-C

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Not relevant

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Major Accident Hazard

Legislation

SEVESO III ACUTE TOXIC

H2

Quantity 1: 50 t Quantity 2: 200 t

SEVESO III

FLAMMABLE LIQUIDS

P5c

Quantity 1: 5.000 t Quantity 2: 50.000 t

Occupational restrictions Take note of Dir 94/33/EC on the protection of young

people at work. Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or

stricter national regulations where applicable.

Regulation (EC) No 1005/2009 on substances not regulated

that deplete the ozone layer

Regulation (EC) No 850/2004 of the

not regulated

European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC

Substances of very high concern (SVHC)

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of \geq 0.1 %

(w/w).

National legislation

Storage class 3

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out.

Page 12 of 14

according to Regulation (EC) No. 1907/2006

Catalogue No. 845088

Product name Ethylamine (70% solution in water) Msynth®plus

SECTION 16. Other information

Full text of H-Statements referred to under sections 2 and 3.

H220 H225	Extremely flammable gas. Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.

Training advice

Provide adequate information, instruction and training for operators.

Labelling

Hazard pictograms







Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H311 + H331 Toxic in contact with skin or if inhaled.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

Precautionary statements

Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P310 IF exposed or concerned: immediately call a POISON CENTER or doctor/physician.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Page 13 of 14

according to Regulation (EC) No. 1907/2006

Catalogue No. 845088

Product name Ethylamine (70% solution in water) Msynth®plus

Contains: Ethylamine

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Regional representation

This information is given on the authorised Safety Data Sheet for your country.

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.