

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Revision Date 19.03.2020

Version 21.11

SECTION 1. Identification of the substance/mixture and of the company/undertaking **1.1** Product identifier

	Catalogue No. Product name	100983 Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur
	REACH Registration Number	01-2119457610-43-XXXX
	CAS-No.	64-17-5
1.2 Relevant identified uses of the substance or mixture and uses advised against		

Identified uses	Reagent for analysis, Chemical production
	In compliance with the conditions described in the annex to
	this safety data sheet.

1.3 Details of the supplier of the safety data sheet

Company	Merck KGaA * 64271 Darmstadt * Germany * Phone:+49 6151 72-0
Responsible Department	LS-QHC * e-mail: prodsafe@merckgroup.com

1.4 Emergency telephone Please contact the regional company representation in your country.

SECTION 2. Hazards identification

2.1 Classification of the substance or mixture Classification (REGULATION (EC) No 1272/2008)

Flammable liquid, Category 2, H225 Eye irritation, Category 2, H319 For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Page 1 of 21



Catalogue No. Product name 100983 Ethanol absolute for analysis EMSURE® ACS, ISO, Reag. Ph Eur

Signal word Danger

Hazard statements H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Precautionary statements
Prevention
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P240 Ground/bond container and receiving equipment.
Response
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
Storage
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Reduced labelling (≤125 ml)

Hazard pictograms



Signal word Danger

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Index-No. 603-002-00-5

2.3 Other hazards

None known.

SECTION 3. Composition/information on ingredients

3.1 Substance

Formula	C₂H₅OH	C2H6O (Hill)
Index-No.	603-002-00-5	
EC-No.	200-578-6	
Molar mass	46,07 g/mol	

Hazardous components (REGULATION (EC) No 1272/2008)

Chemical name (Concentration) CAS-No. Registration Classification number ethanol (<= 100 %) Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

64-17-5 01-2119457610-

Page 2 of 21



Catalogue No. Product name 100983 Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

43-XXXX

Flammable liquid, Category 2, H225 Eye irritation, Category 2, H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

3.2 Mixture

Not applicable

SECTION 4. First aid measures

4.1 Description of first aid measures

After inhalation: fresh air.

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

irritant effects, respiratory paralysis, Dizziness, narcosis, inebriation, euphoria, Nausea, Vomiting

4.3 Indication of any immediate medical attention and special treatment needed No information available.

SECTION 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2), Foam, Dry powder, Water

Unsuitable extinguishing media For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Combustible.

Pay attention to flashback. Forms explosive mixtures with air at ambient temperatures. Vapours are heavier than air and may spread along floors. Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Special protective equipment for firefighters In the event of fire, wear self-contained breathing apparatus.

Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

Page 3 of 21



Catalogue No. Product name

100983 Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

Indications about waste treatment see section 13.

SECTION 7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Observe label precautions.

Advice on protection against fire and explosion Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures Change contaminated clothing. Wash hands after working with substance.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

7.3 Specific end use(s)

See exposure scenario in the Annex to this MSDS.

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

Page 4 of 21



Catalogue No. Product name

100983 Ethanol absolute for analysis EMSURE® ACS, ISO, Reag. Ph Eur

Derived No Effect	Level (DNEL)		
Worker DNEL, acute	Local effects	inhalation	1900 mg/m³
Worker DNEL, longterm	Systemic effects	dermal	343 mg/kg Body weight
Worker DNEL, longterm	Systemic effects	inhalation	950 mg/m ³
Consumer DNEL, acute	Local effects	inhalation	950 mg/m ³
Consumer DNEL,	Systemic effects	dermal	206 mg/kg Body weight
longterm Consumer DNEL, Jongtorm	Systemic effects	inhalation	114 mg/m³
longterm Consumer DNEL, longterm	Systemic effects	oral	87 mg/kg Body weight
	t Concentration (PN	-	
PNEC Fresh water		0,96 mg/l	
PNEC Marine water		0,79 mg/l	
PNEC Fresh water sedime	nt	3,6 mg/kg	
PNEC Soil		0,63 mg/kg	
PNEC Aquatic intermittent	t release	2,75 mg/l	
PNEC Sewage treatment	plant	580 mg/l	
PNEC oral		720 mg/kg	

8.2 Exposure controls

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

<i>Eye/face protect</i> Safety glasses	ion	
Safety glasses		
<i>Hand protection</i> full contact:	Glove material: Glove thickness: Break through time:	butyl-rubber 0,7 mm 480 min
splash contact:	Glove material:	Nitrile rubber

Page 5 of 21

The life science business of Merck operates as $\ensuremath{\mathsf{MilliporeSigma}}$ in the US and Canada



Catalogue No.100983Product nameEthanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

Glove thickness: 0,40 mm Break through time: 120 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 898 Butoject® (full contact), KCL 730 Camatril® -Velours (splash contact).

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not let product enter drains. Risk of explosion.

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	liquid
Colour	colourless
Odour	alcohol-like
Odour Threshold	0,1 - 5058,5 ppm
рН	7,0 at 10 g/l 20 °C
Melting point	-114,5 °C
Boiling point/boiling range	78,3 °C at 1.013 hPa
Flash point	13 °C Method: c.c.

Page 6 of 21



Catalogue No. Product name	100983 Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur
Evaporation rate	No information available.
Flammability (solid, gas)	No information available.
Lower explosion limit	3,1 %(V)
Upper explosion limit	27,7 %(V)
Vapour pressure	59 hPa at 20 °C
Relative vapour density	1,6
Density	0,790 - 0,793 g/cm3 at 20 °C
Relative density	No information available.
Water solubility	at 20 °C completely miscible
Partition coefficient: n- octanol/water	log Pow: -0,31 (experimental) (Lit.) Bioaccumulation is not expected.
Auto-ignition temperature	No information available.
Decomposition temperature	No information available.
Viscosity, dynamic	1,2 mPa.s at 20 °C
Explosive properties	Not classified as explosive.
Oxidizing properties	none
9.2 Other data	
Ignition temperature	425 °C Method: DIN 51794
Conductivity	< 1 µS/cm

SECTION 10. Stability and reactivity

10.1 Reactivity

Vapours may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Page 7 of 21



Catalogue No.100983Product nameEthanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

10.3 Possibility of hazardous reactions

Risk of explosion/exothermic reaction with:

hydrogen peroxide, perchlorates, perchloric acid, Nitric acid, mercury(II) nitrate, permanganic acid, Nitriles, peroxi compounds, Strong oxidizing agents, nitrosyl compounds, Peroxides, sodium, Potassium, halogen oxides, calcium hypochlorite, nitrogen dioxide, metallic oxides, uranium hexafluoride, iodides, Chlorine, Alkali metals, Alkaline earth metals, alkali oxides, Ethylene oxide

silver, with, Nitric acid

silver compounds, with, Ammonia

potassium permanganate, with, conc. sulfuric acid

Risk of ignition or formation of inflammable gases or vapours with:

halogen-halogen compounds, chromium(VI) oxide, chromyl chloride, Fluorine, hydrides, Oxides of phosphorus, platinum

Nitric acid, with, potassium permanganate

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

rubber, various plastics

10.6 Hazardous decomposition products

no information available

SECTION 11. Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity LD50 Rat: 10.470 mg/kg OECD Test Guideline 401

Symptoms: Nausea, Vomiting

Acute inhalation toxicity LC50 Rat: 124,7 mg/l; 4 h ; vapour OECD Test Guideline 403

Symptoms: slight mucosal irritations

Acute dermal toxicity This information is not available.

Skin irritation Rabbit Result: No skin irritation OECD Test Guideline 404

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Page 8 of 21



Catalogue No. Product name

Eye irritation Rabbit Result: Eye irritation OECD Test Guideline 405 Causes serious eye irritation.

Sensitisation Local lymph node assay (LLNA) Mouse Result: negative Method: OECD Test Guideline 429

Germ cell mutagenicity Genotoxicity in vitro Ames test Salmonella typhimurium Result: negative Method: OECD Test Guideline 471 In vitro mammalian cell gene mutation test Mouse lymphoma test Result: negative Method: OECD Test Guideline 476

Carcinogenicity This information is not available.

Reproductive toxicity Application Route: Oral Mouse Method: OECD Test Guideline 416

Teratogenicity This information is not available.

Specific target organ toxicity - single exposure This information is not available.

Specific target organ toxicity - repeated exposure This information is not available.

Aspiration hazard This information is not available.

11.2 Further information

Systemic effects: euphoria After absorption: Dizziness, inebriation, narcosis, respiratory paralysis Other dangerous properties can not be excluded. Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. Ecological information

12.1 Toxicity

The life science business of Merck operates as MilliporeSigma in the US and Canada



Catalogue No. Product name

Toxicity to fish flow-through test EC50 Pimephales promelas (fathead minnow): 15.300 mg/l; 96 h Analytical monitoring: yes US-EPA

Toxicity to daphnia and other aquatic invertebrates EC50 Daphnia magna (Water flea): 9.268 - 14.221 mg/l; 48 h (IUCLID)

Toxicity to algae IC5 Scenedesmus quadricauda (Green algae): 5.000 mg/l; 7 d (Lit.) Toxicity to bacteria

EC5 Pseudomonas putida: 6.500 mg/l; 16 h (IUCLID)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) semi-static test NOEC Daphnia magna (Water flea): 9,6 mg/l; 9 d (ECHA)

12.2 Persistence and degradability

Biodegradability 94 % OECD Test Guideline 301E Readily biodegradable

Biochemical Oxygen Demand (BOD) 930 - 1.670 mg/g (5 d)

(Lit.)

Theoretical oxygen demand (ThOD) 2.100 mg/g

(Lit.)

Ratio COD/ThBOD 90 % (Lit.)

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water log Pow: -0,31 (experimental)

(Lit.) Bioaccumulation is not expected.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

12.6 Other adverse effects

Additional ecological information

No interference with wastewater treatment plants are to be expected when used properly.

Discharge into the environment must be avoided.



Catalogue No. Product name

SECTION 13. Disposal considerations

Waste treatment methods See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14. Transport information

Land transport (ADR/RID))
14.1 UN number	UN 1170
14.2 Proper shipping name	ETHANOL
14.3 Class	3
14.4 Packing group	II
14.5 Environmentally	
hazardous	
14.6 Special precautions for user	yes
Tunnel restriction code	D/E
Inland waterway transpor Not relevant	t (ADN)
Air transport (IATA)	
14.1 UN number	UN 1170
14.2 Proper shipping	ETHANOL
name	2
14.3 Class 14.4 Packing group	3 11
14.4 Packing group 14.5 Environmentally	
hazardous	
14.6 Special precautions	no
for user	
Sea transport (IMDG)	
14.1 UN number	UN 1170
14.2 Proper shipping	ETHANOL
name	-
14.3 Class	3
14.4 Packing group	II
14.5 Environmentally hazardous	
14.6 Special precautions	yes
for user	
EmS	F-E S-D

The life science business of Merck operates as MilliporeSigma in the US and Canada



Page 11 of 21

Catalogue No. Product name

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations		
Major Accident Hazard Legislation	SEVESO III FLAMMABLE LIQUIE P5c	
	Quantity 1: 5.000 t Quantity 2: 50.000	
Occupational restrictions	Take note of Dir 94, people at work.	/33/EC on the protection of young
Regulation (EC) No 1005/ that deplete the ozone lay		not regulated
Regulation (EC) No 850/2 European Parliament and April 2004 on persistent o and amending Directive 7	of the Council of 29 rganic pollutants	not regulated
Substances of very high c	oncern (SVHC)	This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of \geq 0.1 % (w/w).
<i>National legislation</i> Storage class	3	
-		

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out.

SECTION 16. Other information

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.

Training advice

Provide adequate information, instruction and training for operators.

Page 12 of 21



Catalogue No. Product name 100983 Ethanol absolute for analysis EMSURE® ACS, ISO, Reag. Ph Eur

Labelling Hazard pictograms



Signal word Danger

Hazard statements H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Precautionary statements
Prevention
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P240 Ground/bond container and receiving equipment.
Response
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
Storage
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Regional representation

This information is given on the authorised Safety Data Sheet for your country.

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.

Page 13 of 21





Catalogue No. Product name

EXPOSURE SCENARIO 1 (Industrial use)

1. Industrial use Reagent for analysis, Chemical production)

Sectors of end-use

- *SU 3* Industrial uses: Uses of substances as such or in preparations at industrial sites
- SU9 Manufacture of fine chemicals
- *SU 10* Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)

Chemical product category

- PC19 Intermediate
- PC21 Laboratory chemicals

Process categories

- *PROC1* Use in closed process, no likelihood of exposure
- *PROC2* Use in closed, continuous process with occasional controlled exposure
- *PROC3* Use in closed batch process (synthesis or formulation)
- *PROC4* Use in batch and other process (synthesis) where opportunity for exposure arises
- *PROC5* Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)
- *PROC8a* Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities
- *PROC8b* Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
- *PROC9* Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
- *PROC10* Roller application or brushing
- *PROC14* Production of preparations or articles by tabletting, compression, extrusion, pelletisation
- PROC15 Use as laboratory reagent

Environmental Release Categories

- *ERC1* Manufacture of substances
- *ERC2* Formulation of preparations
- *ERC4* Industrial use of processing aids in processes and products, not becoming part of articles
- *ERC6a* Industrial use resulting in manufacture of another substance (use of intermediates)

2. Contributing scenarios: Operational conditions and risk management measures 2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC4, ERC6a

Amount used

Annual amount per site	400000 t
------------------------	----------

Environment factors not influenced by risk management

Flow rate

18.000 m3/d

Page 14 of 21



Catalogue No.	100983
Product name	Ethanol absolute for analysis EMSURE® ACS, ISO, Reag. Ph Eur

Other given operational conditions affecting environmental exposure

Number of emission days per year	350
Emission or Release Factor: Air	70 %
Emission or Release Factor: Water	87 %
Conditions and measures related	d to municipal sewage treatment plant
Type of Sewage Treatment Plant	Municipal sewage treatment plant
Effectiveness (of a measure)	90 %
2.2 Contributing scenario contro	olling environmental exposure for: ERC2
Amount used	
Annual amount per site	75000 t
Environment factors not influen	
Flow rate	18.000 m3/d
Other given operational condition Number of emission days per year	ons affecting environmental exposure 300

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant	Municipal sewage treatment plant
Effectiveness (of a measure)	90 %

2.3 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC14, PROC15

Product characteristics Concentration of the Substance in Mixture/Article Physical Form (at time of use)	Covers the percentage of the substance in the product up to 100 % (unless stated differently). High volatile liquid
Frequency and duration of use Frequency of use	8 hours/day
Other operational conditions aff Outdoor / Indoor	
	beyond the REACH Chemical Safety Assessment Wear suitable gloves (tested to EN374) and eye protection.

Page 15 of 21

The life science business of Merck operates as $\ensuremath{\mathsf{MilliporeSigma}}$ in the US and Canada



Catalogue No. Product name

3. Exposure estimation and reference to its source

Environment

Use descriptor	Msafe	Compartment	RCR	Exposure Assessment Method
ERC1		Fresh water	< 0,01	ECETOC TRA
		Marine water	< 0,01	ECETOC TRA
		Soil	< 0,01	ECETOC TRA
ERC4		Fresh water	< 0,01	ECETOC TRA
		Marine water	< 0,01	ECETOC TRA
		Soil	< 0,01	ECETOC TRA
ERC6a		Fresh water	< 0,01	ECETOC TRA
		Marine water	< 0,01	ECETOC TRA
		Soil	< 0,01	ECETOC TRA
ERC2		Fresh water	0,11	ECETOC TRA
		Marine water	0,01	ECETOC TRA
		Soil	< 0,01	ECETOC TRA
	ERC1 ERC4 ERC6a	ERC1 ERC4 ERC6a	ERC1 Fresh water Marine water Soil ERC4 Fresh water Marine water Soil ERC6a Fresh water Marine water Soil ERC6a Fresh water Marine water Soil	ERC1 Fresh water < 0,01



Catalogue No. Product name 100983 Ethanol absolute for analysis EMSURE® ACS, ISO, Reag. Ph Eur

Workers

CS	Use descriptor	Exposure duration, route, effect	RCR	Exposure Assessment Method
2.3	PROC1	longterm, inhalative, systemic	< 0,01	ECETOC TRA 3
		longterm, dermal, systemic	< 0,01	ECETOC TRA 3
		longterm, combined, systemic	< 0,01	
2.3	PROC2	longterm, inhalative, systemic	0,05	ECETOC TRA 3
		longterm, dermal, systemic	< 0,01	ECETOC TRA 3
		longterm, combined, systemic	0,05	
2.3	PROC3	longterm, inhalative, systemic	0,10	ECETOC TRA 3
		longterm, dermal, systemic	< 0,01	ECETOC TRA 3
		longterm, combined, systemic	0,10	
2.3	PROC4	longterm, inhalative, systemic	0,20	ECETOC TRA 3
		longterm, dermal, systemic	0,02	ECETOC TRA 3
		longterm, combined, systemic	0,22	
2.3	PROC5	longterm, inhalative, systemic	0,50	ECETOC TRA 3
		longterm, dermal, systemic	0,04	ECETOC TRA 3
		longterm, combined, systemic	0,54	
2.3	PROC8a	longterm, inhalative, systemic	0,50	ECETOC TRA 3
		longterm, dermal, systemic	0,04	ECETOC TRA 3
		longterm, combined, systemic	0,54	
2.3	PROC8b	longterm, inhalative, systemic	0,30	ECETOC TRA 3
		longterm, dermal, systemic	0,04	ECETOC TRA 3
		longterm, combined, systemic	0,34	
2.3	PROC9	longterm, inhalative, systemic	0,40	ECETOC TRA 3
		longterm, dermal, systemic	0,02	ECETOC TRA 3
		longterm, combined, systemic	0,42	
2.3	PROC10	longterm, inhalative, systemic	0,50	ECETOC TRA 3
		longterm, dermal, systemic	0,08	ECETOC TRA 3
		longterm, combined, systemic	0,58	
2.3	PROC14	longterm, inhalative, systemic	0,50	ECETOC TRA 3
		longterm, dermal, systemic	0,01	ECETOC TRA 3
		longterm, combined, systemic	0,51	
2.3	PROC15	longterm, inhalative, systemic	0,10	ECETOC TRA 3
		longterm, dermal, systemic	< 0,01	ECETOC TRA 3
		longterm, combined, systemic	0,10	

The default parameters and -efficiencies of the applied exposure assessment model were used for the calculation (unless stated differently).

Page 17 of 21

Catalogue No.100983Product nameEthanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Chapter R.12: Use descriptor system; ECHA Guidance for downstream users; ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

For scaling of worker exposure assessments performed with ECETOC TRA, please consult the Merck tool ScIDeEx® at www.merckmillipore.com/scideex.

Page 18 of 21

The life science business of Merck operates as MilliporeSigma in the US and Canada



Catalogue No. 100983 Product name Ethanol absolute for analysis EMSURE® ACS, ISO, Reag. Ph Eur

EXPOSURE SCENARIO 2 (Professional use)

1. Professional use Reagent for analysis, Chemical production)

Sectors of end-use

SU 22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category

PC21 Laboratory chemicals

Process categories

PROC15 Use as laboratory reagent

Environmental Release Categories

ERC2 Formulation of preparations ERC6a Industrial use resulting in manufacture of another substance (use of intermediates)

2. Contributing scenarios: Operational conditions and risk management measures 2.1 Contributing scenario controlling environmental exposure for: ERC2

Amount used

75000 t Annual amount per site

Environment factors not influenced by risk management Flow rate

18.000 m3/d

Other given operational conditions affecting environmental exposure Number of emission days per 300 vear

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Municipal sewage treatment plant Plant Effectiveness (of a measure) 90 %

2.2 Contributing scenario controlling environmental exposure for: ERC6a

Amount used Annual amount per site	400000 t
Environment factors not influence	ed by risk management
Flow rate	18.000 m3/d
• •	ns affecting environmental exposure
Other given operational condition Number of emission days per year	ns affecting environmental exposure 350
Number of emission days per	-

The life science business of Merck operates as MilliporeSigma in the US and Canada



Page 19 of 21

Catalogue No. Product name	100983 Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur
Emission or Release Factor: Water	87 %
Conditions and measures relate	ed to municipal sewage treatment plant
Type of Sewage Treatment Plant	Municipal sewage treatment plant
Effectiveness (of a measure)	90 %
2.3 Contributing scenario contr	olling worker exposure for: PROC15
Product characteristics	
Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use)	High volatile liquid
Frequency and duration of use	
Frequency of use	8 hours/day

Additional good practice advicebeyond the REACH Chemical Safety AssessmentAdditional good practice
adviceWear suitable gloves (tested to EN374) and eye
protection.

3. Exposure estimation and reference to its source

Environment

CS	Use descriptor	Msafe	Compartment	RCR	Exposure Assessment Method
2.1	ERC2		Fresh water Marine water Soil	0,11 0,01 < 0,01	ECETOC TRA ECETOC TRA ECETOC TRA
2.2	ERC6a		Fresh water Marine water Soil	< 0,01 < 0,01 < 0,01	ECETOC TRA ECETOC TRA ECETOC TRA

Workers

CS	Use descriptor	Exposure duration, route, effect	RCR	Exposure Assessment Method
2.3	PROC15	longterm, inhalative, systemic	0,10	ECETOC TRA 3
		longterm, dermal, systemic	< 0,01	ECETOC TRA 3
		longterm, combined, systemic	0,10	

The default parameters and -efficiencies of the applied exposure assessment model were used for the calculation (unless stated differently).



Page 20 of 21

Catalogue No. Product name

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Chapter R.12: Use descriptor system; ECHA Guidance for downstream users; ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

For scaling of worker exposure assessments performed with ECETOC TRA, please consult the Merck tool ScIDeEx® at www.merckmillipore.com/scideex.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

