

SAFETY DATA SHEET

Creation Date 13-Nov-2013 Revision Date 26-Jan-2018 Revision Number 4

1. Identification

Product Name Methyl methacrylate

Cat No.: AC127140000; AC127140010; AC127140025; AC127140100;

AC127140250

CAS-No 80-62-6 Synonyms MMA

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Acros Organics
One Reagent Lane One Reagent Lane
Fair Lawn, NJ 07410 Fair Lawn, NJ 07410

Tel: (201) 796-7100

Emergency Telephone Number

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Skin Sensitization

Category 2

Category 2

Category 2

Category 2

Category 1

Specific target organ toxicity (single exposure)

Category 3

Target Organs - Respiratory system.

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor Causes skin irritation

Causes serious eye irritation
May cause an allergic skin reaction
May cause respiratory irritation



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Skin

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Methyl methacrylate	80-62-6	>95

4. First-aid measures

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Revision Date 26-Jan-2018 Methyl methacrylate

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. In the case of skin irritation or allergic reactions see a physician.

Inhalation Remove from exposure, lie down. Remove to fresh air. If not breathing, give artificial

respiration. Get medical attention.

Ingestion Do NOT induce vomiting. Clean mouth with water. Get medical attention.

Most important symptoms and

effects

May cause allergic skin reaction. Difficulty in breathing. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness,

lightheadedness, chest pain, muscle pain or flushing: Inhalation of high vapor

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting

Treat symptomatically **Notes to Physician**

Fire-fighting measures

Suitable Extinguishing Media Carbon dioxide (CO₂). Foam. Dry chemical. Water mist may be used to cool closed

containers. Water mist may be used to cool closed containers.

Unsuitable Extinguishing Media No information available

8 °C / 46.4 °F **Flash Point**

No information available Method -

Autoignition Temperature 430 °C / 806 °F

Explosion Limits

Upper 12.5% Lower 2.1%

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO2).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health **Flammability** Instability Physical hazards 2 3 N/A

Accidental release measures

Personal Precautions Environmental Precautions Remove all sources of ignition. Take precautionary measures against static discharges. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

Up

Methods for Containment and Clean Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal, Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Do not let this chemical enter the

environment.

7. Handling and storage

Handling

Avoid contact with skin and eyes. Do not breathe mist/vapors/spray. Handle product only in closed system or provide appropriate exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Keep away from open flames, hot surfaces and sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage

Keep in a dry, cool and well-ventilated place. Refer product specification and/or product label for specific storage temperature requirement. Keep container tightly closed. Keep away from heat, sparks and flame. Refrigerator/flammables.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Methyl methacrylate	TWA: 50 ppm	(Vacated) TWA: 100 ppm	IDLH: 1000 ppm	TWA: 50 ppm
	STEL: 100 ppm	(Vacated) TWA: 410 mg/m ³	TWA: 100 ppm	STEL: 100 ppm
		TWA: 100 ppm	TWA: 410 mg/m ³	
		TWA: 410 mg/m ³	_	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists
OSHA - Occupational Safety and Health Administration
NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Eye/face Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorStrong

Odor Threshold
pH
No information available
No information available
No information available
48 °C / -54.4 °F

Boiling Point/Range 100 °C / 212 °F @ 760 mmHg
Flash Point 8 °C / 46.4 °F

Evaporation Rate

Flammability (solid.gas)

No information available
Not applicable

Flammability or explosive limits

Upper 12.5%

Revision Date 26-Jan-2018 Methyl methacrylate

Lower 2.1%

Vapor Pressure 40 mbar @ 20 °C **Vapor Density** 3.5 (Air = 1.0)**Specific Gravity** 0.930

Solubility

No information available Partition coefficient; n-octanol/water No data available 430 °C / 806 °F **Autoignition Temperature Decomposition Temperature** No information available 0.6 mPa s at 20 °C Viscosity

C5 H8 O2 Molecular Formula **Molecular Weight** 100.12

10. Stability and reactivity

Reactive Hazard Yes

Stable under normal conditions. Hazardous polymerization may occur upon depletion of Stability

inhibitor.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition. Excess heat. Exposure

to light. Incompatible products.

Incompatible Materials Acids, Bases, Amines, Halogens, Peroxides, Reducing Agent

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization may occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information Component Information

Component initiation			
Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl methacrylate	LD50 8420 - 10000 mg/kg (Rat) LD50 = 7872 mg/kg (Rat)	LD50 5000 - 7500 mg/kg (Rabbit) LD50 > 5 g/kg (Rabbit)	LC50 = 7093 ppm (Rat) 4 h

Toxicologically Synergistic No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes, respiratory system and skin

Sensitization May cause sensitization by skin contact

The table below indicates whether each agency has listed any ingredient as a carcinogen. Carcinogenicity

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Methyl methacrylate	80-62-6	Not listed				

Mutagenic Effects Mutagenic effects have occurred in experimental animals.

Reproductive Effects Experiments have shown reproductive toxicity effects on laboratory animals.

Developmental Effects No information available. No information available. **Teratogenicity**

STOT - single exposure Respiratory system

Revision Date 26-Jan-2018 Methyl methacrylate

STOT - repeated exposure None known

Aspiration hazard No information available

delayed

Symptoms / effects, both acute and Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not empty into drains. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment. Contains a substance which is:. Harmful to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methyl methacrylate	EC50: = 170 mg/L, 96h	LC50: 326.4 - 426.9 mg/L,	Not listed	EC50: = 69 mg/L, 48h
	(Pseudokirchneriella	96h static (Poecilia		(Daphnia magna)
	subcapitata)	reticulata)		
		LC50: > 79 mg/L, 96h static		
		(Oncorhynchus mykiss)		
		LC50: > 79 mg/L, 96h		
		flow-through (Oncorhynchus		
		mykiss)		
		LC50: 153.9 - 341.8 mg/L,		
		96h static (Lepomis		
		macrochirus)		
		LC50: 170 - 206 mg/L, 96h		
		flow-through (Lepomis		
		macrochirus)		
		LC50: 125.5 - 190.7 mg/L,		
		96h static (Pimephales		
		promelas)		
		LC50: 243 - 275 mg/L, 96h		
		flow-through (Pimephales		
		promelas)		

Persistence and Degradability Persistence is unlikely

Bioaccumulation/ Accumulation No information available.

Mobility . Will likely be mobile in the environment due to its water solubility.

Component	log Pow
Methyl methacrylate	0.7

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl methacrylate - 80-62-6	U162	-

14. Transport information

DOT

UN1247 **UN-No**

Proper Shipping Name METHYL METHACRYLATE MONOMER, STABILIZED Hazard Class 3

Packing Group

_TDG

UN-No UN1247

Proper Shipping Name METHYL METHACRYLATE MONOMER, STABILIZED

Hazard Class 3
Packing Group ||

IATA

UN-No UN1247

Proper Shipping Name METHYL METHACRYLATE MONOMER, STABILIZED

Hazard Class 3 Packing Group II

IMDG/IMO

UN-No UN1247

Proper Shipping Name METHYL METHACRYLATE MONOMER, STABILIZED

Hazard Class 3
Packing Group ||

15. Regulatory information

United States of America Inventory

	Component	CAS-No	TSCA	TSCA Inventory notification -	TSCA - EPA Regulatory
				Active/Inactive	Flags
ľ	Methyl methacrylate	80-62-6	X	ACTIVE	-

Legend:

TSCA - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Australia (AICS), China (IECSC), Korea (ECL).

Component	CAS-No	DSL	NDSL	EINECS	PICCS	ENCS	AICS	IECSC	KECL
Methyl methacrylate	80-62-6	Х	-	201-297-1	X	X	Х	Х	KE-25050

U.S. Federal Regulations

SARA 313

0,, 10.10				
Comp	onent	CAS-No	Weight %	SARA 313 - Threshold Values %
Methyl me	thacrylate	80-62-6	>95	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Methyl methacrylate	X	1000 lb	-	-

Clean Air Act

	Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Ī	Methyl methacrylate	X		-

OSHA - Occupational Safety and

Health Administration

Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs	
Methyl methacrylate	1000 lb	-	

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know

Regulations

	Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Γ	Methyl methacrylate	X	X	Χ	Χ	X

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 13-Nov-2013

 Revision Date
 26-Jan-2018

 Print Date
 26-Jan-2018

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS