

| Cat. No.  | h (mm) | Neck  | DN  | ID Flange (mm) | Outer diameter (AD) Flange (mm) | Pack Unit |
|-----------|--------|-------|-----|----------------|---------------------------------|-----------|
| 244204605 | 62     | 24/29 | 100 | 119            | 153 ± 2                         | 1         |
| 244205704 | 85     | 24/29 | 150 | 172            | 215 ± 2                         | 1         |
| 244206109 | 94     | 24/29 | 200 | 224            | 270 ± 2                         | 1         |
| 244206606 | 109    | 24/29 | 250 | 274            | 320 ± 2                         | 1         |
| 244206906 | 137    | 24/29 | 300 | 332            | 380 ± 2                         | 1         |

## DURAN® Desiccator Lid

for standard ground joint stopcocks (NS 24/29), type NOVUS, suitable for all types of bases




DIN ISO  
13130

| Cat. No.  | h (mm) | DIN Thread (GL) | DN  | ID Flange (mm) | Outer diameter (AD) Flange (mm) | Pack Unit |
|-----------|--------|-----------------|-----|----------------|---------------------------------|-----------|
| 244405709 | 85     | 32              | 150 | 172            | 215 ± 2                         | 1         |
| 244406105 | 94     | 32              | 200 | 224            | 270 ± 2                         | 1         |
| 244406602 | 109    | 32              | 250 | 274            | 320 ± 2                         | 1         |
| 244406902 | 137    | 32              | 300 | 332            | 380 ± 2                         | 1         |

## DURAN® Desiccator Lid

with threaded outlet, type MOBILEX (GL 32), suitable for all bases




DIN ISO  
13130

Ordering advice: the O-ring is dimensioned according to the groove diameter:

| Cat. No.                | d (mm) | DN  | s (mm) | Pack Unit |
|-------------------------|--------|-----|--------|-----------|
| 292245709               | 174    | 150 | 5.7    | 1         |
| 292246002               | 229    | 200 | 5.7    | 1         |
| 292246602               | 274    | 250 | 6.5    | 1         |
| for articles since 1996 |        |     |        |           |
| 292155703               | 185    | 150 | 5.3    | 1         |
| 292156108               | 236    | 200 | 5.3    | 1         |
| 292156605               | 290    | 250 | 5.3    | 1         |

## O-Ring

suitable for desiccators, from silicone (VMQ)



Tmax.  
200 °C