KERN FCB3K0.1

Bench scale with second display on the backside of the scale





Measuring system	
Adjustment options:	External calibration
Linearity:	300 mg
Readability [d]:	100 mg
Recommended adjusting weight:	2 kg (M1); 1 kg (M1)
Repeatability:	100 mg
Resolution:	30000
Stabilisation time under laboratory conditions:	3 s
Tare range:	3 kg
Warm up time:	2 h
Weighing capacity [Max]:	3 kg
Weighing system:	Strain gauge
Weighing units:	dwt g lb mo oz ozt tl (HK) tl (Tw) tol

Display digit height:	2,500 cm
Counting	
Counting resolution:	15000
Mininum piece weight at piece counting (Laboratory:	200 mg
Mininum piece weight at piece counting (Normal):	2 g

Display

Functions		
Counting function:	yes	
Percentage determination:	yes	
Vibration-free weighing (Animal weighing program):	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5°C

Power supply	
Battery:	9 V Block
Charging time:	10 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	CH EURO UK US
Operating time:	12 h
Operating time (Backlight off):	10 h
Operating time (Backlight on):	5 h
Rechargeable battery:	Rchrg. battery optional

	\triangle	W	/1	\sim	6
O	v	l BA	ин	u	Œ

Adjustment at the location of installation: 961-247


DAkkS Certificate: 963-127

Category	
Brand:	KERN
Category:	Balances
Product Group:	Bench scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	400 x 340 x 190 mm
Gross weight:	3,250 kg
Net weight:	2,590 kg
Shipping method:	Parcel service

Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	270 x 323 x 110 mm
Dimensions of weighing plate (WxDxH):	252 x 228 x 110 mm
Material weighing plate:	stainless steel
Weighing surface (WxD):	253 x 227 mm

KERN FCB3K0.1





Piktogramme

STANDARD



OPTION

