

“MaXcrub™ T1” Glass/Labware Washer, Max 95 °C, Washing Surface 0.52m², 400Lit/min, Max 5bar
with 1 × STS Wire Basket, Water-/Detergent-/Distilled Water-Auto Injection, Program Washing Cycle, Double Wall, Telescopic Rail, **초자 세척기**



2-Year Warranty

Glass/Labware Washer “MaXcrub™ T1”

- **Made in Korea** ■ **PL(Product Liability) Insurance.**
- **with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System.**
- **Ideal for Clinical, Pharmaceutical, Bioresearch, Chemical Research, etc.**
- **Outstanding Fast Washing Cycle and High-performance Cleaning Results from Efficient Direct Injection Washing.**
- **Water-/Detergent-/Distilled Water- Automatically Injected into Wash Chamber via Pumps.**
- **Double Layer Wall ensures Soundproof and Heatproof.**
- **Automatic Door Lock system for User Safety.**
- **Special Steam Condensing Mechanism for User Safety.**

- * Built-in Telescopic Sliding Rail for Safety and Easy to Use.
- * Provides Efficient Program Washing Cycle : Pre-set 6 Programs and Customizable 1Program.
- * Built-in Steam Condenser Prevents Steam to enter into the Laboratory.
- * Included 1ea STS Wire Basket .
- * Customizable Various Rack, Basket, Pipette Rack, Volumetric Flask Rack, Direct Injection Kit, etc.

Specifications & Ordering information

Spec.	Model	“MaXcrub™ T1”
Total Washing Surface		0.52m ²
Temp. Range		Room Temp +5°C to 95°C
Display		Digital LCD with Back-Light Function
Controller		Digital Fuzzy-Control System (Fully Automatic), Touch Button UI
Programmable Function		Pre-set 6 Programs & Customizable 1 Programs
Wash Pump		Recirculation : 400Lit/min, Water Pressure : 3~5bar, Water Consumption : 8~10Lit.
Rack		Included 1ea Stainless-steel Standard Rack
Safety Circuit		Over-Temp./-Pressure/-Current protection, Sensor Error Detection
Material		Stainless-steel (#304)-Internal, Stainless steel (#304)-External
Dimension (w × d × h)	Interior	508 × 515 × h407 mm
	Exterior	600 × 625 × h870 mm
Power Consumption		5 kW
Net Weight		95 kg
Electric Reqts.		1 Phase, AC 120 V, 60 Hz or AC 230 V, 50 / 60 Hz

Cat. No.	60Hz	230V	DH.WGW0400
		120V	DH.WGW0401
	50Hz	230V	DH.WGW5400

Price, Each. ₩

* Other Specifications are available upon Customer's Request.

※ **Note! Freight and Installation Charges Separately.**

Spare Stainless-steel Standard Rack

DH.WGW01001 (1) STS Wire Basket, for Rail, 495 × 510mm

Ea. Price, ₩

Optional Stainless-steel Injection Rack for Various Vessel

DH.WGW01002 (2) STS Injection Rack for Various Vessel, 495 × 510mm **New**

Ea. Price, ₩

Optional Liquid Cleaning Detergent & Rinse

DH.WGW02010 (3) Potassium Hydroxide Liquid Cleaning Detergent, 18Lit.

Ea. Price, ₩

DH.WGW02011 (4) Nonionic Surfactant Liquid Rinse, 18Lit.

Ea. Price, ₩

Optional Customizable Various Rack/Basket/Direct Injection Kit



2-Year Warranty

Glass/Labware Washer “MaXcrub™ T1”
with Optional Customizing Rack



(1) (Included) STS Wire Basket



(2) Optional STS Injection Rack



(3) Cleaner (4) Rinse
Optional Liquid Detergents