

## SAFETY DATA SHEET

Creation Date 10-Nov-2010

Revision Date 19-Jan-2018

Revision Number 3

### 1. Identification

**Product Name** n-Butylamine

**Cat No. :** AC107800000; AC107800010; AC107800025; AC107800050;  
AC107800100; AC107802500

**CAS-No** 109-73-9  
**Synonyms** 1-Aminobutane

**Recommended Use** Laboratory chemicals.  
**Uses advised against** Not for food, drug, pesticide or biocidal product use

#### Details of the supplier of the safety data sheet

##### Company

Fisher Scientific  
One Reagent Lane  
Fair Lawn, NJ 07410  
Tel: (201) 796-7100

Acros Organics  
One Reagent Lane  
Fair Lawn, NJ 07410

##### **Emergency Telephone Number**

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

### 2. Hazard(s) identification

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Acute oral toxicity	Category 4
Acute dermal toxicity	Category 3
Acute Inhalation Toxicity - Dusts and Mists	Category 3
Skin Corrosion/irritation	Category 1 A
Serious Eye Damage/Eye Irritation	Category 1
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system.	

#### Label Elements

##### **Signal Word**

Danger

##### **Hazard Statements**

Highly flammable liquid and vapor  
Harmful if swallowed  
Toxic in contact with skin  
Toxic if inhaled  
Causes severe skin burns and eye damage

May cause respiratory irritation



### Precautionary Statements

#### Prevention

Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

#### Response

Immediately call a POISON CENTER or doctor/physician

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

#### Skin

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

#### Ingestion

Rinse mouth

Do NOT induce vomiting

#### Fire

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

#### Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

None identified

## 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Butylamine (n-)	109-73-9	>95

## 4. First-aid measures

### General Advice

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Immediate medical attention is required.
<b>Inhalation</b>	Move to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If not breathing, give artificial respiration.
<b>Ingestion</b>	Do not induce vomiting. Call a physician or Poison Control Center immediately.
<b>Most important symptoms and effects</b>	Breathing difficulties. Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting; Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation
<b>Notes to Physician</b>	Treat symptomatically

## 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed containers exposed to fire with water spray.
<b>Unsuitable Extinguishing Media</b>	No information available
<b>Flash Point</b>	-7 °C / 19.4 °F
<b>Method -</b>	No information available
<b>Autoignition Temperature</b>	290 °C / 554 °F
<b>Explosion Limits</b>	
<b>Upper</b>	9.8 vol %
<b>Lower</b>	1.7 vol %
<b>Sensitivity to Mechanical Impact</b>	No information available
<b>Sensitivity to Static Discharge</b>	No information available

### Specific Hazards Arising from the Chemical

Flammable. Corrosive Material. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Thermal decomposition can lead to release of irritating gases and vapors. Containers may explode when heated. Keep product and empty container away from heat and sources of ignition.

### Hazardous Combustion Products

Nitrogen oxides (NO<sub>x</sub>) Carbon monoxide (CO) Carbon dioxide (CO<sub>2</sub>)

### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### NFPA

<b>Health</b>	<b>Flammability</b>	<b>Instability</b>	<b>Physical hazards</b>
3	3	0	N/A

## 6. Accidental release measures

<b>Personal Precautions</b>	Wear self-contained breathing apparatus and protective suit. Evacuate personnel to safe areas. Remove all sources of ignition. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Take precautionary measures against static discharges.
<b>Environmental Precautions</b>	Should not be released into the environment. See Section 12 for additional ecological information. Do not flush into surface water or sanitary sewer system.

**Methods for Containment and Clean Up** Wear self-contained breathing apparatus and protective suit. Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

## 7. Handling and storage

**Handling** Use only under a chemical fume hood. Wear personal protective equipment. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Do not ingest. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

**Storage** Keep away from heat and sources of ignition. Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area.

## 8. Exposure controls / personal protection

### Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Butylamine (n-)	Ceiling: 5 ppm Skin	Ceiling: 5 ppm Ceiling: 15 mg/m <sup>3</sup> Skin (Vacated) Ceiling: 5 ppm (Vacated) Ceiling: 15 mg/m <sup>3</sup>	IDLH: 300 ppm Ceiling: 5 ppm Ceiling: 15 mg/m <sup>3</sup>	Ceiling: 5 ppm Ceiling: 15 mg/m <sup>3</sup>

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

**Engineering Measures** Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

### Personal Protective Equipment

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

**Skin and body protection** Wear appropriate protective gloves and clothing to prevent skin exposure.

**Respiratory Protection** Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

<b>Physical State</b>	Liquid
<b>Appearance</b>	Colorless
<b>Odor</b>	Ammonia-like
<b>Odor Threshold</b>	No information available

pH	12.6 100g/l aq.sol
Melting Point/Range	-49 °C / -56.2 °F
Boiling Point/Range	78 °C / 172.4 °F
Flash Point	-7 °C / 19.4 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	9.8 vol %
Lower	1.7 vol %
Vapor Pressure	93 hPa @ 20 °C
Vapor Density	2.5 (Air = 1.0)
Specific Gravity	0.740
Solubility	No information available
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	290 °C / 554 °F
Decomposition Temperature	No information available
Viscosity	0.5 mPa.s at 20 °C
Molecular Formula	C4 H11 N
Molecular Weight	73.13

## 10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Acids, Metals, copper
Hazardous Decomposition Products	Nitrogen oxides (NO <sub>x</sub> ), Carbon monoxide (CO), Carbon dioxide (CO <sub>2</sub> )
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

## 11. Toxicological information

### Acute Toxicity

#### Product Information Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Butylamine (n-)	LD50 = 366 mg/kg ( Rat )	LD50 = 850 µL/kg ( Rabbit )	LC50 2000 - 4000 ppm ( Rat ) 4 h

**Toxicologically Synergistic Products** No information available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	Causes severe burns by all exposure routes
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Butylamine (n-)	109-73-9	Not listed	Not listed	Not listed	Not listed	Not listed

**Mutagenic Effects** Not mutagenic in AMES Test

**Reproductive Effects** No information available.

<b>Developmental Effects</b>	No information available.
<b>Teratogenicity</b>	No information available.
<b>STOT - single exposure</b>	Respiratory system
<b>STOT - repeated exposure</b>	None known
<b>Aspiration hazard</b>	No information available
<b>Symptoms / effects, both acute and delayed</b>	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation
<b>Endocrine Disruptor Information</b>	No information available
<b>Other Adverse Effects</b>	The toxicological properties have not been fully investigated.

## 12. Ecological information

### Ecotoxicity

This product contains the following substance(s) which are hazardous for the environment. Contains a substance which is: Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Butylamine (n-)	Not listed	LC50: = 32 mg/L, 96h static (Lepomis macrochirus) LC50: = 32 mg/L, 96h semi-static (Lepomis macrochirus) LC50: = 26.8 mg/L, 96h flow-through (Pimephales promelas) LC50: = 268 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 24.8 mg/L 30 min EC50 = 28.5 mg/L 15 min EC50 = 41.1 mg/L 5 min	EC50: = 43 mg/L, 24h (Daphnia magna) EC50: = 75 mg/L, 24h Static (Daphnia magna)

**Persistence and Degradability** Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Will likely be mobile in the environment due to its volatility.

Component	log Pow
Butylamine (n-)	0.97

## 13. Disposal considerations

**Waste Disposal Methods** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

## 14. Transport information

### DOT

<b>UN-No</b>	UN1125
<b>Proper Shipping Name</b>	N-BUTYLAMINE
<b>Hazard Class</b>	3
<b>Subsidiary Hazard Class</b>	8
<b>Packing Group</b>	II

### TDG

UN-No UN1125  
 Proper Shipping Name N-BUTYLAMINE  
 Hazard Class 3  
 Subsidiary Hazard Class 8  
 Packing Group II

**IATA**

UN-No UN1125  
 Proper Shipping Name n-BUTYLAMINE  
 Hazard Class 3  
 Subsidiary Hazard Class 8  
 Packing Group II

**IMDG/IMO**

UN-No UN1125  
 Proper Shipping Name BUTYLAMINE  
 Hazard Class 3  
 Subsidiary Hazard Class 8  
 Packing Group II

## 15. Regulatory information

**International Inventories**

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Butylamine (n-)	X	X	-	203-699-2	-		X	X	X	X	X

**Legend:**

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

**U.S. Federal Regulations**

TSCA 12(b) Not applicable

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

**CWA (Clean Water Act)**

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Butylamine (n-)	X	1000 lb	-	-

Clean Air Act Not applicable

OSHA Occupational Safety and Health Administration  
Not applicable

**CERCLA** This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Butylamine (n-)	1000 lb	-

**California Proposition 65** This product does not contain any Proposition 65 chemicals

#### U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Butylamine (n-)	X	X	X	-	X

#### U.S. Department of Transportation

Reportable Quantity (RQ): N  
 DOT Marine Pollutant N  
 DOT Severe Marine Pollutant N

#### U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

#### Other International Regulations

**Mexico - Grade** Serious risk, Grade 3

### 16. Other information

**Prepared By** Regulatory Affairs  
 Thermo Fisher Scientific  
 Email: EMSDS.RA@thermofisher.com

**Creation Date** 10-Nov-2010

**Revision Date** 19-Jan-2018

**Print Date** 19-Jan-2018

**Revision Summary** This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**